




APMAG1210K

MAGNUM OPTIMUM FOLDABLE PALLET BOX WITH SKIDS

Our Magnum Optimum® 1210 is suitable for a variety of applications and is the strongest foldable large container (FLC) on the market. Its double-wall structure offers more volume than other similar containers, while its high folding ratio helps to reduce the cost of reverse logistics. The Magnum Optimum 1210 features unique self-locking doors which makes it easy to use. A variety of accessories, including lids, dust covers and our unique Optiframe are also available. A single Optiframe increases the height of the container in increments of 105 mm. The Magnum Optimum 1210 can be tracked & traced using SmartLink® or RFID. Available in a wide variety of heights, base and sidewall configurations, the possibilities with Magnum Optimum® 1210 are endless.



Specifications

External max length (L):	1200 mm
External max width (W):	1000 mm
External max height (H):	975 mm
External max height folded (H2):	325 mm
Internal min Length (Li):	1140 mm
Internal min Width (Wi):	940 mm
Internal Usable Height (Hi):	790 mm
Folding Ratio:	68.8 %
Incremental Stack Height Folded (H2a):	295 mm
Incremental stack height (Ha):	945 mm
Net weight kg:	51 kg
Usable Volume:	847 L
Individual Load Capacity:	750 kg
Max Static Load on Bottom Product of a Stack:	3200 kg
Max Dynamic Load on Bottom Product of a Stack:	1600 kg
Max static stacking quantity erected:	5
Max static stacking quantity folded:	20
Max dynamic stacking quantity folded:	10
Max dynamic stacking quantity erected:	3
Base Type:	solid base with drainage holes
Long side wall type:	Solid
Short side wall type:	Solid
Drain Holes:	9
Suitable for automated handling:	No
Main Material:	PP POM PE (Label Holder)
Operational Temperature Range:	-20 °C - 40 °C